



SAIPH

GHID DE INSTALARE

INSTALLATION GUIDE

RO / EN

0

RO

- A: Scoateti panourile laterale si panoul frontal.
- B: Instalati sursa de alimentare.
- C: Instalati placa de baza.
- D: Instalati ventilatoarele.
- E: Instalati HDD-ul sau SSD-ul (hard-disk drive/solid-state drive).
- F: Instalati placa grafica (VGA).

EN

- A: Remove the side panels and front panel.
- B: Install the power supply (PSU).
- C: Install the motherboard (MB).
- D: Install the fans.
- E: Install the hard-disk drive or the solid-state drive (HDD or SSD).
- F: Install the graphics card (VGA).

Accesorii incluse / Included accessories

1 x8 2 x1 3 x11 4 x4 5 x5 6 x8 7 x3

A

RO

- Va rugam sa desurubati suruburile inainte de scoaterea panourilor laterale.
- Va rugam sa scoateti panourile laterale inainte sa scoateti panoul frontal.

EN

- Please remove the screws before removing the side panels.
- Please remove the side panels before removing the front panel.

B

1

RO

- Inainte de montarea sursei va rugam sa scoateti suportul acesteia din carcasa.

EN

- Please remove the PSU frame before installation.

2

RO

- Va rugam sa va asigurati ca gaurile de prindere pentru suruburi sunt pozitionate corect.

EN

- Please make sure that the threaded holes are positioned correctly.

3

RO

- Dupa fixarea sursei in suportul dedicat, o puteti instala in carcasa conform imaginii de mai sus.

EN

- After attaching the frame to the PSU, you can install the PSU inside the case, as shown above.

C

RO

- Aliniati gaurile placii de baza cu distantierele din cupru si fixati folosind suruburile Nr.3. Daca unul din distantiere lipseste, adaugati un distantier nou Nr.2.

EN

- Align the MB holes with the copper spacers and secure using the No.3 screws. If one of the spacers is missing, add a new spacer (No.2).

D

RO

- Ventilatoare acceptate (maxim):
 - Frontal: 2 x 120mm
 - Spate: 2 x 120mm
 - Tavan: 2 x 120mm
- Pentru performante superioare carcasa permite folosirea unui sistem de racire cu lichid, oferind posibilitatea instalarii radiatoarelor:
 - Frontal: 120 / 240mm (radiatoare slim)
 - Tavan: 120 / 240mm (radiatoare slim)
 - Spate: 120mm (radiatoare slim)

EN

- Supported fans (maximum):
 - Front: 2 x 120mm
 - Back: 2 x 120mm
 - Top: 2 x 120mm
- For superior performance, the chassis allows the use of a liquid cooling system, offering the possibility of installing radiators:
 - Front: 120 / 240vmm (slim radiators)
 - Top: 120 / 240mm (slim radiators)
 - Back: 120mm (slim radiators)

E

1

RO

- Pentru instalarea HDD-ului in suportul dedicat, respectati ilustratia 1.
- Pentru instalarea SSD-ului-urilor in suportul dedicat, respectati ilustratia 2.

EN

- For HDD installation in the dedicated slot, please follow illustration 1.
- For SSD installation in the dedicated slot, please follow illustration 2.

F

1

RO

- Scoateti capacul de protectie al sloturilor PCI. Instalati placa grafica si fixati-o cu surub.

EN

- Remove the PCI slot protection cover. Install the graphics card and secure it with a screw.

